



DENATURED ALCOHOL

PURE VIRGIN SOLVENT

Denatured Alcohol is used in various aspects of industry. Denatured Alcohol is used in the paint and coatings manufacturing process. This solvent can be used for many reasons such as paint and coating clean-up for tools and accessories, paint thinning, coating, re-emulsification for the purpose of fixing faulty applications or conditions, etc.

Specifications / Compliances



Typical Properties & Technical Information

PROPERTY	VALUE
Solids/Active Content, Percentage by weight	0%
Dry Time - Tack Free	Depends on Solvent
Dry Time - Foot Traffic	Depends on Solvent
Dry Time - Heavy Traffic	Depends on Solvent
Re-Coat Time Window	Depends on Solvent
Application Temperature	50° F - 80° F
VOC (Volatile Organic Compound) Content	Depends on Solvent
Appearance - Wet	Clear
Appearance - Dry	N/A

Information above is based on lab temperatures of 70° - 72°F at 50% RH. Using this product outside these conditions may affect the accuracy of the information above. Always test prior to use!

ALWAYS REFER TO SDS & READ FULL TECH DATA SHEET AND WARRANTY INFORMATION PRIOR TO USE.

KEY FEATURES & TYPICAL BENEFITS

- Superior cleaning capabilities and re-emulsification properties of solvent based coatings.
- Excellent options for thinning many solvent based sealers.
- Dry times vary for many different applications.
- Low VOC and VOC free solvents available.

RECOMMENDED APPLICATIONS

Effective on applications such as...

- Use Denatured Alcohol for clean-up
- Many other uses for solvents and low VOC solvents

LOW VOC PRODUCT

FOR PROFESSIONAL USE ONLY



DENATURED ALCOHOL

APPLICATION INSTRUCTIONS

SURFACE PREP: Instructions vary due to extensive amount of uses. Please contact the supplier for details pertaining to your specific application.

MIXING: No mixing necessary prior to use.

COVERAGE RATE: *First Coat*: Varies depending upon application
*Coverage rates vary depending upon surface porosity and texture, and application method.

APPLICATION: Instructions vary due to extensive amount of uses. Please contact the supplier for details pertaining to your specific application.

FOR PERSONAL PROTECTION USE GLOVES, GOGGLES, AND RESPIRATORS

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc.

PRECAUTIONS AND LIMITATIONS

- This product will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- Keep away from open flames. Product is flammable and is very susceptible to ignition.
- This product may affect the surface of many new and existing concrete slabs. Test prior to use.
- This product is harmful if swallowed. Abide by recommended safety guidelines.
- This product is not a stripper and may not emulsify acrylic, epoxy, urethane, or any other coating.
- This product does not make existing coatings resistant to brake fluid, gasoline, and many similar products.
- SOLVENT VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.

CLEAN-UP: Dispose of containers in accordance with local, state and federal regulations.

PRODUCT REMOVAL: Not applicable.

SHELF LIFE: Up to one year from manufacture date in its original, unopened container stored at room temperature.

PACKAGING: Available in 1 gallon, 5 gallon and 55 gallon containers.

Always read all technical information, label and SDS prior to use. This information can be found online or by calling customer service at the number below.

The manufacturer warrants our products to be of good quality, free of defects and will conform with our published specifications in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, we will replace defective materials. Ninety days after the manufacturer has shipped the products, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product, or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will the manufacturer be liable for a consequential damage to anyone in excess of the purchase price of the products.